



TexWalk

THE SOLUTION FOR INDOOR COMMUNICATION

TexWalk is the ultimate, one-step solution for indoor floors and walls and for short-term outdoor use on smooth surfaces. TexWalk works great on carpet, tile, wood, metal & painted surfaces and is ideal for tradeshow and POP graphics.

Uses

- Applied on top of carpeting, tiles, wooden and PVC floors and untreated stone
- Sidewalk graphics
- Wall graphics
- Door coverage
- Tradeshows (exhibition walls and floor)

Features & Benefits

- Structured matte finish
- Little to no adhesive residue
- Sticks on almost any surface
- Easy to apply and remove
- Slip resistant - ASTM D-2047 & R12 certificate
- Print and go - no laminate solution
- Digital cutting into any shape



info@digitalcolorink.com
www.asphaltartusa.com



Digital
Color_{ink}



TexWalk

THE SOLUTION FOR INDOOR COMMUNICATION

Printing & Application

TexWalk is inkjet printable via solvent, eco-solvent, uv-curable or latex inks. Application surface must be dry, clean and above 50°F before application.

Durability

TexWalk will last up to 3 months on indoor floor applications, depending on the type of traffic. Indoor wall applications will last 24-36 months. Outdoor sidewalk applications last 1-3 months.

Storage

It is recommended to store the product in closed packaging at a temperature of +60°F to +85°F (+15°C to +30°C) and humidity range of 45% to 60%. The product has a shelf life of 24 months.

Warranty

Asphalt Art products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the Technical Specifications Sheets. Asphalt Art will replace or refund the price of any Asphalt Art materials found to not meet our product specifications. In no case shall Asphalt Art be liable for any direct, indirect, or consequential damages, including labor or non-Asphalt Art materials charges.

Technical information

| | |
|---------------------------------|--|
| Roll Sizes: | 48"x 82' (1.22m x 25m) |
| Material: | 8mil white, textured, matte vinyl with fabric backing & repositionable, solvent acrylic adhesive |
| Slip-Resistance Certifications: | ASTM D-2047 & Euro-Norm R12 |



TexWalk

is an opaque white material



info@digitalcolorink.com
www.asphaltartusa.com